

Tapes and Measuring Wheels





Lufkin® Table of Contents

Contents	Page No.
EC-Standardization	59
Power Tapes	60 - 63
Pocket Tapes	64 - 65
Long Tapes	66 - 68
Fiberglass Tapes	69
Measuring wheels	70 - 71
Lufkin® Numerical Index	187




EC-Standardization

Each Lufkin measure tape (steel) corresponds to the Class II of the European Weights and Measure Regulations (except CME tapes and HY-series). Tolerance of dimensional accuracy in $mm \pm is$ for the whole tape length.

Class	1 m	2 m	3 m	5 m	10 m	15 m	20 m	30 m	50 m	
I	0,2	0,3	0,4	0,6	1,1	1,6	2,1	3,1	5,1	
Ш	0,5	0,7	0,9	1,3	2,3	3,3	4,3	6,3	10,3	
III	1,0	1,4	1,8	2,6	4,6	6,6	8,6	12,6	20,6	

The tolerance has been determined at a temperature of 20°C and a power of 50 Newton.

The tolerances of measure tapes of Class I and Class II are determined by the following formula.



L = nominal length in meter

	a	b
Class I:	0,1	0,1
Class II:	0.3	0.2

Example:

3 m tapes / EC-Class II: $(0.3 + 0.2 \times 3) = \pm 0.9$ mm difference



Series P1000



- Bright Hi-Viz® orange case Easy to find on the Job
- Rubber cushion case exterior protects tape from Impact and improves grip
- Fits easily into most tape holsters
- Bright yellow blade has clear easy-to Read numerals
- Toggle lock is positioned for convenient operation
- Holds the blade securely in any position
- Cushioned blade return

		Blade Siz	ze	Weight	Shelf
Type / Code No.	Packed	Width	Length	g	Pack
PHV1023CME	Carded	13 mm/ ¹ / ₂ "	3 m/10'	130	6
PHV1035CM	Carded	19 mm	5 m	280	6
PHV1035CME	Carded	19 mm/ ³ / ₄ "	5 m/16'	280	6
PHV1410CME	Carded	25 mm/1"	10 m/33'	600	6
PHV1048CME	Carded	25 mm/1"	8 m/26'	480	6
PHV1048DM	Carded	1"	26'	480	6

Series 2000



- Ergonomic design, rounded case to feel as if it was part of the hand.
- High strength case with removable belt clip.
- Blade lock placed on top where the thumb expects it to be.
- Lock holds blade securely at any length.
- Unbreakable end hook and bright, clean graphics.
- Built-in shock absorber cushions blade return.

			Blade	Size	Weight	Shelf	Replacement Bl	ade	Shelf
Туре	Code No.	Packed	Width	Length	g	Pack	Туре	Code No.	Pack
2003	T0069200304	Carded	16 mm	3 m	135	6	R2003	T0069221704	6
2105	T0069210504	Carded	16 mm	5 m	191	6	R2105	T0069221707	6
2205	T0069220504	Carded	19 mm	5 m	230	6	RY35CM	T0063803504	6
2208	T0069220804	Carded	25 mm	8 m	439	6	RY48CM	T0063804804	6



Ultralok

- Chrome-plated lightweight high strength case.
- Blade lock holds blade at any length.
- Powered blade return
- Built-in shock absorber cushions blade return.
- Removable belt clip



			Blade S	ize	Weight	Shelf	Replacement Blade		Shelf
Туре	Code No.	Packed	Width	Length	g	Pack	Туре	Code No.	Pack
Y23CM	T0060402304	Carded	13 mm	3 m	110	6	RY23CM	T0063802304	6
Y23CME	T0060402311	Carded	13 mm/ ¹ / ₂ "	3 m/10'	110	6			
Y25CM	T0060402504	Carded	13 mm	5 m	160	6	RY25CM	T0063802504	6
Y25CME	T0060402511	Carded	13 mm/ ¹ / ₂ "	5 m/16'	160	6			
Y35CM	T0060403504	Carded	19 mm	5 m	205	6	RY35CM	T0063803504	6
Y35CME	T0060403511	Carded	19 mm/ ³ / ₄ "	5 m/16'	205	6	RY35CME	T0063803511	6
Y38CM	T0060403804	Carded	19 mm	8 m	335	6	RY38CM	T0063803804	6
Y38CME	T0060403811	Carded	19 mm/ ³ / ₄ "	8 m/26'	335	6			

Unilok

- Black high strength case
- Blade lock holds blade at any length.
- Powered blade return
- Built-in shock absorber cushions blade return.
- Removable belt clip



Туре	Code No.	Packed	Blade S Width	ize Length	Weight g	Shelf Pack	Replacement Blade Type	Code No.	Shelf Pack
YU823CM	T0061082304	Carded	13 mm	3 m	110	6	RY23CM	T0063802304	6
YU823CME	T0061082311	Carded	13 mm/ ¹ / ₂ "	3 m/10'	110	6			
YU835CM	T0061083504	Carded	19 mm	5 m	202	6	RY35CM	T0063803504	6
YU835CME	T0061083511	Carded	19 mm/ ³ / ₄ "	5 m/16'	202	6	RY35CME	T0063803511	6
YU838CM	T0061083804	Carded	19 mm	8 m	323	6	RY38CM	T0063803804	6
YU838CME	T0061283811	Carded	19 mm/ ³ / ₄ "	8 m/26'	323	6			



Series 500



- Good value at a low price.
- Durable ABS case, contour shape fits comfortably in hand.
- Hi-Viz® colour makes it easy to find.
- Unique slide lock for easy control.
- Triple-riveted (5 m and 8 m) respectively double-riveted (3 m)
- Reinforced end-hook
- Belt clip

		Blade Size	Blade Size		Shelf	
Type / Code No.	Packed	Width	Length	g	Pack	
L503CM	Carded	13 mm	3 m	107	6	
L505CM	Carded	19 mm	5 m	209	6	
L508CM	Carded	25 mm	8 m	403	6	

Series 600





- Lightweight, High Strength,
- Case Fits Comfortably in Hand
- Hi-Viz Case
- Easy to find on the Job
- Unique Slide Lock Design allows for Easy Control of Tape Blade
- Wide Base Helps Keep Tape Standing Upright
- Clear Coat Blade Protection for More Durable Markings
- Easy to Read Yellow Clad Blade

		Blade Size	Blade Size			
Type / Code No.	Packed	Width	Length	g	Pack	
L610CME	Carded	13 mm/ ¹ / ₂ "	3 m/10'	107	6	
L616CME	Carded	19 mm/ ³ / ₄ "	5 m/16'	209	6	
L625CME	Carded	25 mm/1"	8 m/26'	403	8	

Series 700 - Magnetic End Hook





- Series 700 metric
- Unique slide lock for easy control.
- Rubber coated TPR (Thermo Plastic Rubber) case for more comfort.
- Hi-Viz® colour makes it easy to find.
- Belt clip
- L748MAG with magnetic end hook.
 A time saver for framers, HV/AC installers and more

		Blade Size		Weight	Shelf
Type / Code No.	Packed	Width	Length	g	Pack
L748MAG	Carded	25 mm/1'	8 m/26'	360	8



Series 800 - Control

- Drag Strip finger access for measuring nad retraction control
- Wide end-hook holds better and makes marking easier
- New blade design achieves 10 ft Stand-out, make longer measurements
- Clearcoat blade protection more durable markings
- Durable case allows for added control and grip
- Integrated D-ring for tether strap or easy handling storage
- Easy On/Off belt clip for fast attachment to belt



		Blade Size	Blade Size		Shelf	
Type / Code No.	Packed	Width	Length	g	Pack	
CS8525CME	Carded	30mm / ³ / ₁₆ "	8m / 26'	600	6	

Focus

- Ergonomic high strength case, Hi-Viz® colour orange.
- New type of scale marking can be read from both the left and the right.
- Blade lock holds blade at any length.
- Powered blade return
- Built-in shock absorber cushions blade return.
- New developed "Quad" hook (on 25 mm / 1" tape only) ensures long life.
- Removable belt clip



	Blade Size				Weight	Shelf
Туре	Code No.	Packed	Width	Length	g	Pack
W48CM	T0069104804	Carded	25 mm	8 m	420	6



Universal



- Small and compact
- Blade lock holds blade at any length
- Powered blade return
- High strength case
- With removable belt clip

			Blade S	ize	Weight	Shelf	Replacement Blade		Shelf
Туре	Code No.	Packed	Width	Length	g	Pack	Туре	Code No.	Pack
Y822CM	T0061182204	Carded	13 mm	2 m	66	6	RY22CM	T0063802204	6
Y822CME	T0061182211	Carded	13 mm/ ¹ / ₂ "	2 m/6'	66	6			
Y823CM	T0061182304	Carded	13 m	3 m	92	6	RY23CM	T0063802304	6
Y823CME	T0061182311	Carded	13 mm/ ¹ / ₂ "	3 m/10'	92	6			

Mezurall in Metal Case



- Attractive, rugged zinc alloy case
- Ideal for industrial use
- Power retraction operation

			Blade S	Size	Weight	Shelf	Replacement Blade		Shelf
Туре	Code No.	Packed	Width	Length	g	Pack	Туре	Code No.	Pack
Y422CM	T0060842204	Carded	13 mm	2 m	120	6	RY22CM	T0063802204	6
Y423CM	T0060842304	Carded	13 mm	3 m	140	6	RY23CM	T0063802304	6
Y423CME	T0060842311	Carded	13 mm/ ¹ / ₂ "	3 m/10'	140	6			



Mezurall in Chrome Plated Plastic Case

- Chrome-plated high strength plastic case
- Power retraction operation
- Belt clip



			Blade	Size	Weight	Shelf
Туре	Code No.	Packed	Width	Length	g	Pack
W9312D	W9312D	Carded	3/4"	12'	167	6

Pee Wee


- Pocket size ideal for office and home
- High strength case in black
- Power retraction operation
- Blade is not replaceable



			Blade	Size	Weight	Shelf
Туре	Code No.	Packed	Width	Length	g	Pack
Y612CM	T0061561254	Boxed	6 mm	2 m	30	25
Y613CM	T0061561354	Boxed	6 mm	3 m	40	25

Executive® Diameter

- Designed for measuring diameters of pipe, cable, tire or any circular object.
- Polished chrome case
- Zero falls in the same place on each side of the blade.
- Model W606PD shows diameter inches to 100ths, W606PM to millimetres.
- Yellow clad tape
- Easy-to-read bold graduations on yellow background.
- Spring action returns blade to case.







Banner



- Traditional design
- Professional tradesmans' quality
- Rugged, vinyl-covered steel case
- Large easy action winding drum and friction washers.
- Nylon rollers guide the tape smoothly in and out of case.
- "YB" prefix denotes product blade is fitted with a ring, zero point 10 cm behind ring.
- "HY" prefix denotes product blade is fitted with a hook ring, zero point at inner side of hook ring.

			Blade	Size	Weight	Shelf	Replacement Blade		Shelf
Туре	Code No.	Packed	Width	Length	g	Pack	Туре	Code No.	Pack
YB210CM	T0061821004	Carded	10 mm	10 m	357	1			
YB220CM	T0061822004	Carded	10 mm	20 m	602	1	RYB220CM	T0064022004	1
YB230CM	T0061823004	Carded	10 mm	30 m	762	1			
YB250CM	T0061825004	Carded	10 mm	50 m	1136	1			

Special



		Blade Siz	ze	Weight	Shelf
Type / Code No.	Packed	Width	Length	g	Pack
LS10CM	Carded	10 mm	10 m	250	6
LS20CM	Carded	10 mm	20 m	370	6
LS30CM	Carded	10 mm	30 m	518	6
LS10CME	Carded	10 mm/ ³ / ₈ "	10 m/33'	250	6
LS20CME	Carded	10 mm/ ³ / ₈ "	20 m/66'	370	6
LS30CME	Carded	10 mm/ ³ / ₈ "	30 m/100'	518	6



Speedwinder Tapes

- 3:1 Gear ratio for fast blade retrieval.
- Precise, easy to read black and red blade markings.
- High-impact ABS case with non-slip grip.



		Blade Size		Weight	Shelf
Type / Code No.	Packed	Width	Length	g	Pack
SW20CM	Carded	10 mm	20 m	422	6
SW30CM	Carded	10 mm	30 m	530	6
SW20CME	Carded	10 mm/ ³ / ₈ "	20 m/66'	422	6
SW30CME	Carded	10 mm/ ³ / ₈ "	30 m/100'	530	6

Speedwinder Hi-Viz

- Impact-resistant, attractive, self-standing case
- Heavy duty yellow clad blade protected by an abrasion resistant coating
- Extends, rewinds in less time than conventional long steel tapes
- Easy-to-read bold black markings



		Blad	Blade Size		Shelf	
Type / Code No.	Packed	Width	Length	g	Pack	
HYT100D	Boxed	3/8"	100'	680	6	



Frame Tapes



Type / Code No.	Packed	Blade Si Width	ze Length	Weight g	Shelf Pack	Replacement Blade Type / Code No.
FT30CM	Carded	13 mm	30 m	648	6	RFT30CM
FT50CM	Carded	13 mm	50 m	850	6	
FT30CME	Carded	13 mm/ ¹ / ₂ "	30 m/100'	648	6	
FT50CME	Carded	13 mm/ ¹ / ₂ "	50 m/150'	850	6	



Hi-Viz® Linear Reel

- Lightweight open reel is easy to handle and rewind.
- Line does not collect dirt in case.
- Hi-Viz® orange case
- 2-Sided tape, Metric/English (Feet)



		Blade S	Size	Weight	Shelf
Type / Code No.	Packed	Width	Length	g	Pack
FM030CME	Carded	13 mm/ ¹ / ₂ "	30 m / 100'	540	1
FM050CME	Carded	13 mm/ ¹ / ₂ "	50 m / 164'	790	1

Hi-Viz® Linear Reel

- Sturdy open case
- · Long handle for fast and effortless rewinding.
- Hi-Viz® orange case
- 2-Sided tape, Metric/English (Feet)



		Blade S	Size	Weight	Shelf	
Type / Code No.	Packed	Width	Length	g	Pack	
FM100CME	Carded	13 mm/ ¹ / ₂ "	100 m / 328'	1520	1	

Pro Series Fiberglass Tapes

- Interchangeable end hooks for user convenience
- Ring end hook snaps onto stake for 1-person measurements
- Standard folding end hook for general measuring needs
- Appraiser's hook attaches to oversized objects such as downspouts
- 3-to-1 rewind for fast blade retraction
- 3/4" blade is more durable; large numbers are easy to read
- 2-sided blade, feet & inches on top, feet to 10ths and 100ths on bottom
- 62 fiberglass strands and double-pvc coating for durability and strength
- Cushion grips on handle and frame arms for comfort





		Blade S	Size	Weight	Shelf
Type / Code No.	Packed	Width	Length	g	Pack
PSFE100	Carded	3/4"	100'	1150	2
PSFE200	Carded	3/4"	200'	1700	2
PSFE300	Carded	3/4"	300'	2150	2
PSFM060CME	Carded	19 mm / ³ / ₄ "	60 m / 200'	1700	2



Measuring Wheels



- Measuring wheel, dual foldable, up to 9999,9 mm
- Wheel diameter 160 mm, calibrated to counter
- Wheel brake and counter reset in handle
- Compact, foldable design
- Rubber molded handle
- Carry bag included
- Centimeters and Meters

			Tool weight	Shelf
Code No.	Description	Packed	g	Pack
MW16MEU	Measuring Wheel, \varnothing 160 mm / 6 $^{1}/_{8}$ "	Boxed	1100	1



Measuring Wheels

- Measuring wheel, foldable, up to 9999,9 m
- Wheel diameter 318 mm, calibrated to counter
- Wheel brake and counter reset in handle
- Built-in kickstand
- Size folded 650 mm, extended 1059 mm
- Rubber molded handle
- Feet and inches



			Tool weight	Shelf
Code No.	Description	Packed	g	Pack
PSMW38	Measuring Wheel, ø 318 mm / 12 $^{1}/_{2}$ "	Carded	1600	2

Measuring Wheels

- Reset trigger in handle and counter
- Braking trigger in handle
- Patented hinge mechanism handle for storage, folded size 530 mm
- Full-cushion tire for improved traction
- 5 digit counter measures 10.000 m without resetting, 10 cm steps
- Built in kickstand wheel
- Large 305 mm wheel diameter provides more accurate measurements particularly on uneven terrain
- Comfortable handling, total length: 980 mm
- Centimeters and Meters



Code No.	Description	Packed	Tool weight g	Shelf Pack
MW30MEU	Measuring Wheel 305mm/12"	Boxed	1720	4



Notes

