

**TEST CERTIFICATE
& DECLARATION
OF CONFORMITY**

TO MACHINERY DIRECTIVE
2006/42/EC & 1492-2

BaTo®

CERTIFICATE No.

ZS-25J319

ORDER No.


7912

**Description of Goods
Round Sling
Material: 100% Polyester
Safety Factor: 7:1**

(1) Serial No.	(2) WLL(kg)	(3) Effective Working Length(m)	(4) Color
2504686 ~ 2504745	5000	3	Red

**We hereby certify that the above mentioned products have been inspected
and tested to comply with the health and safety requirements of the Machinery
Directive 2006/42/EC**

lifeng Yu



Date:08/2025

Brugsanvisning for Polyester Rundsling

BATO®

WLL: 5000 kg

EWL: 3 m



Belastningstabel:

SAFE LIFTING CHART - WORKING LOAD LIMIT IN Kg							
Colour code according to EN 1492-2	Straight Lift	Choke Hitch	Basket Hitch			Multi-Leg Slings	
			0-7°	7-45°	45-60°	0-45°	0-45°
WLL Factor	1.0	0.8	2.0	1.4	1.0	1.4	2.0
WLL 1000Kg	1000	800	2000	1400	1000	1400	2000
WLL 2000Kg	2000	1600	4000	2800	2000	2800	4000
WLL 3000Kg	3000	2400	6000	4200	3000	4200	6000
WLL 4000Kg	4000	3200	8000	5600	4000	5600	8000
WLL 5000Kg	5000	4000	10000	7000	5000	7000	10000
WLL 6000Kg	6000	4800	12000	8400	6000	8400	12000
WLL 8000Kg	8000	6400	16000	11200	8000	11200	16000
WLL 10000Kg	10000	8000	20000	14000	10000	14000	20000
WLL 12000Kg	12000	9600	24000	16800	12000	16800	24000
WLL 15000Kg	15000	12000	30000	21000	15000	21000	30000
WLL 20000Kg	20000	16000	40000	28000	20000	28000	40000
WLL 30000Kg	30000	24000	60000	42000	30000	42000	60000

Brugsanvisning

- Vurder løfteevne ved de forskellige løftemåder.
- Bruges mere end en båndstrop til løft, skal de være identiske.
- Hold stroppen væk fra syrer og baser.
- Beskyt stroppen mod skarpe kanter og friktion.
- Temperatur: -40° til + 100°.
- Lav aldrig knude på stroppen.

Instruktioner for inspektion

- Undersøg nøje stroppen før brug.
- Brug ikke stroppen hvis der findes noget af følgende:
 - Revner
 - Visuel inderkerne
 - Syre/base skader
 - Løse syninger
 - Varme skader