

**TEST CERTIFICATE
& DECLARATION
OF CONFORMITY**

TO MACHINERY DIRECTIVE
2006/42/EC & 1492-1

BaTo[®]

CERTIFICATE No.

ZS-25J319

ORDER No.


7912

Description of Goods
Webbing Sling
Material: 100% Polyester
Safety Factor: 7:1

(1) Serial No.	(2) WLL(kg)	(3) Effective Working Length(m)	(4) Color
2505596 ~ 2505875	1000	4	Purple

We hereby certify that the above mentioned products have been inspected and tested to comply with the health and safety requirements of the Machinery Directive 2006/42/EC

lifeng Yu



Date:08/2025

Brugsanvisning for Polyester Båndstropper

BATO®

WLL: 1000 kg

Length: 4 m



Belastningstabel:

SAFE LIFTING CHART - WORKING LOAD LIMIT IN Kg

Colour code according to EN 1492-1	Straight Lift	Choke Hitch	Basket Hitch			Multi-Leg Slings	
			0-7°	7-45°	45-60°	0-45°	0-45°
WLL Factor	1.0	0.8	2.0	1.4	1.0	1.4	2.0
WLL 1000Kg	1000	800	2000	1400	1000	1400	2000
WLL 2000Kg	2000	1600	4000	2800	2000	2800	4000
WLL 3000Kg	3000	2400	6000	4200	3000	4200	6000
WLL 4000Kg	4000	3200	8000	5600	4000	5600	8000
WLL 5000Kg	5000	4000	10000	7000	5000	7000	10000
WLL 6000Kg	6000	4800	12000	8400	6000	8400	12000
WLL 8000Kg	8000	6400	16000	11200	8000	11200	16000
WLL 10000Kg	10000	8000	20000	14000	10000	14000	20000

Brugsanvisning

- Vurder løfteevne ved de forskellige løftemåder.
- Bruges mere end en båndstrop til løft, skal de være identiske.
- Hold stroppen væk fra syrer og baser.
- Beskyt stroppen mod skarpe kanter og friktion.
- Temperatur: -40° til + 100°.
- Lav aldrig knude på stroppen.

Instruktioner for inspektion

- Undersøg nøje stroppen før brug.
- Brug ikke stroppen hvis der findes noget af følgende:
 - Revner
 - Visuel inderkerne
 - Syre/base skader
 - Løse syninger
 - Varme skader