



BGS Alternator Bit and Socket Set | 23 pcs.

- special bit set with alternator combination sockets (also for air conditioning compressors), for assembly and disassembly of the freewheel pulley

scope of delivery:

- multi-tooth 15 mm, 33 tooth, Ø17.5 mm socket
- multi-tooth 15 mm, 33 tooth, Ø19.5 mm socket
- multi-tooth 22 mm, 33 tooth, Ø19.5 mm socket
- adapter for pulley wrench, 19 mm and 28 mm
- adapter for pulley wrench, 22 mm and 28 mm
- 3-pin adapter, external hex drive 38 mm
- 4-pin adapter, external hex drive 17 mm
- bits, length 70 mm, hexagon 10 mm drive, hexagon H10 mm
- bits, length 75 mm, external hexagon drive 10 mm (3/8"), hexagon socket 8 and 10 mm,
- bits length 75 mm, external hexagon drive 10 mm (3/8"), spline (for XZN) M8 and M10
- bits, length 75 mm, external hexagon drive 10 mm (3/8"), T-star (for Torx) T40 and T50
- bit adapter with retaining ball, square 12.5 mm (1/2") drive hexagon socket 10 mm (3/8")
- bit socket for alternator, external hex drive 12 mm, spline (for XZN) M10
- bit socket, length 90 mm, 10 mm (3/8") drive, spline (for XZN) M10
- bit socket, length 110 mm, 12.5 mm (1/2") drive, spline (for XZN) M10
- bit socket, length 140 mm, 12.5 mm (1/2") drive, spline for XZN) M10
- bit socket, length 110 mm, 12.5 mm (1/2") drive, T-star (for Torx) T50
- Special insert, external hex drive 17 mm
- special socket, external hex drive 21 mm
- special socket, external hex drive 22 mm and 28 mm
- incl. adapter for BMW, Fiat, Ford, Mercedes-Benz, Opel / Vauxhall, Porsche, Renault, Toyota, VAG etc.

Weight: 2,808 kg.